

## 光电倍增管模块

ETL也可提供多种尺寸的光电倍增管模块，可选择圆形和方形尺寸，内部PMT有效直径可选尺寸:25mm和22mm。

### 主要特点:

- 出厂前预先设置，达到最佳性能
- 动态范围广（最高100Mcps）
- 带电磁和静电屏蔽
- 光谱范围可选



### 主要型号和参数:

TTL信号输出系列:

型号	光谱范围 (nm)	有效直径 (mm)	暗计数典型值 (cps)
PDM03-9107-TTL	280-630	25	100
PDM04-9111-TTL	280-630	22	100
PDM04-9113-TTL	280-850	22	3000
PDM9107-CP-TTL	280-630	25	100
PDM9107-AP-TTL	280-630	25	100
PDM9111-CP-TTL	280-630	22	100
PDM9113-CP-TTL	280-850	22	3000

USB输出系列:

型号	光谱范围 (nm)	有效直径 (mm)	暗计数典型值 (cps)
PDM03-9107-USB	280-630	25	100
PDM04-9108-USB	280-680	25	200
PDM04-9111-USB	280-630	22	100
PDM04-9113-USB	280-850	22	3000
PDM9107-USB	280-630	25	100
PDM9111-USB	280-630	22	100
PDM9113-USB	280-850	22	3000

## 光电倍增管相关配件

